U.S. National Phase Application of International Application PCT/CZ2004/000090

International Filing Date: 23 December 2004

Preliminary Amendment

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application. The

amendment is taken from the claims as set forth in International Publication No. WO 2005/071256.

Listing of Claims.

1. (Currently amended) A rolling fluid machinæspecially with a liquid spraying at the output,

comprising:

a chamber (1) having an inner surface, where at least a part of its said inner surface has a

rotary shape and the chamber (1) is provided with at least one fluid inlet (2) of fluid

and at least one <u>fluid</u> outlet (3) of fluid, while in the chamber; and

a rolling rotor (4) is installed mounted in the chamber to provide a clearance between the

rotor and the inner surface in a manner enabling rolling and swinging, characterized

by the fact that in the chamber (1)

wherein, a first the space (5) is provided in the chamber below bellow the rotor (4) and a

second space is provided in the chamber above the rotor, and wherein the first space

below the rotor and the second space (6) above the rotor (4) is are fluidically

interconnected by at least one additional channel in addition to the clearance.

2. (currently amended) The rolling fluid machine as set forth in Claim 1, wherein the rotor

includes a wall and wherein the additional channel (7) comprises an opening trough through the wall

of the rotor (4).

U.S. National Phase Application of International Application PCT/CZ2004/000090 International Filing Date: 23 December 2004

Preliminary Amendment

3. (currently amended) The rolling fluid machine as<u>set forthin Claim 1</u>, wherein the <u>chamber includes an inner space and wherein the additional channel (7) is arranged outside the inner space of the chamber (1).</u>

- 4. (currently amended) The rolling fluid machine as <u>set forth</u> in any of the above Claims 1 to

 3 <u>Claim 1</u>, wherein the <u>additional</u> channel (7) <u>includes</u> <u>has incorporated</u> a control valve (8) <u>incorporated</u> therein.
- 5. (currently amended) The rolling fluid machine as set forth in Claim 2, wherein the additional channel (7) is connected to the a hollow shaft mounting the rotor in the chamber.
- 6. (new) The rolling fluid machine as set forth in Claim 2, wherein the channel includes a control valve incorporated therein.
- 7. (new) The rolling fluid machine as set forth in Claim 3, wherein the channel includes a control valve incorporated therein.

U.S. National Phase Application of International Application PCT/CZ2004/000090

International Filing Date: 23 December 2004

Preliminary Amendment

Remarks

This is a National Phase application under 35 USC §371 et seq of International Application

PCT/CZ2004/000090. Claims 1-5 remain in this application and have been amended from the

claims as presented in the published international application in order to conform to U.S. practice,

including the elimination of multiple dependent claims, and to provide certain antecedents for

structural matters as set forth in the claims. No new matter has been added. In view of the favorable

International Search Report, it is now believed that this application is in condition for allowance and

such is courteously requested. Should any additional fees be necessitated by this submission, they

may be charged to Deposit Account 19-0522. Any issues which may be resolved by a telephone

conference may be addressed to the undersigned at 1-800-445-3460.

Respectfully submitted,

HOVEY WILLIAMS LLP

Thomas H. Van Hoozer, Reg. #32761

Suite 400

2405 Grand Boulevard

Kansas City, Missouri 64108

(816) 474-9050

(Docket No. 37351)

U.S. National Phase Application of International Application PCT/CZ2004/000090

International Filing Date: 23 December 2004

Preliminary Amendment

Abstract

A rolling fluid machine especially with a liquid spraying at the output, comprising includes a

chamber (1) where at least a part of its inner surface has a rotary shape and teh chamber (1) is

provided with at least one inlet (2) of fluid and at least one outlet (3) of fluid. In the chamber (1),

there is a rolling rotor (4) installed in a manner enabling rolling and swinging. In the chamber (1),

the space (5) below the rotor (4) and the space above the rotor (4) is interconnected by at least one

additional channel (7).

Docket 37351

Page 6 of 6